

TECHNICAL DATA SHEET

Sound Curtain Enclosure UN-10 CV Windows

Unger Technologies offers noise barrier clear view windows. The vinyl windows constructed are 1-lb psf vinyl barrier. Curtain panels are constructed with grommets across the top and Velcro along the vertical edges. Rolls are available 54" wide x 25' long and can be supplied with edges bound or unbound (note: barrier is 54" wide, quilt is held 3" in from each vertical edge, and measures 48")

- Class A (or 1) flammability rated per ASTM E84
- Available facing colors: gray, white, black, or tan
- Available barrier colors: gray, tan, or blue

Applications:

Typically used as curtain panels in acoustical curtain enclosures where abuse resistance or excellent durability is required. Frequently used as partition walls and sliding doors on acoustical curtain enclosures. Also, preferred for use in outdoor applications, as well as a durable acoustical wrap.



Acoustical Performance:

Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
<u>UN-10 CV</u>	11	16	24	30	35	30	27

ASTM E-90 & E 413

Unger Technologies, Inc.
 297 North 9th Street, Noblesville, IN 46060
 PH: 888.213.4711