

129 Penn St  
Westfield, IN 46074  
info@eNoiseControl.com  
Ph: 317.774.1900



8' x 8' STC 48 Double-Leaf Door piggy-backed onto larger STC 60, fire rated, projectile rated, blast rated door—paired with an STC 62, projectile and blast resistant 4' x 8' window system.  
Wixom, MI



APR Vehicle Entry Door, 10' x 10' STC 50 Double-Leaf Doors  
Opelika, AL

### Single-Leaf, Double-Leaf or Bi-Fold Designs

- Test Facilities
- Engine Test Cells
- Quiet Rooms
- Product Jury Rooms
- Vibration Test Labs
- Mechanical Equipment Rooms
- Machinery Enclosures
- Control Rooms
- Conference Rooms
- Secure Areas
- Sensitive Compartmented  
Information Facilities (SCIF)
- Factory Offices
- Test Chambers
- Shake—Rattle—Roll Rooms
- Power Generation
- Compressor Rooms
- Gen. Set Rooms

## Features

## Industrial Doors

**eNoise Control can provide for all your sound control door needs.**

- Guaranteed acoustic performance
- All doors are tested at Riverbank Laboratories or USG Testing Services Lab, both are independent NVLAP approved testing facilities
- All hardware, seals and hinges are factory installed
- Door includes custom cam-lift hinge design, eliminating the need for a threshold in most applications
- Adjustable mortised bottom seal allows the door to adapt to site floor conditions
- Double magnetic seals at head and jambs
- Split-frame assembly allows installation into existing openings
- All doors with vision panels are factory glazed prior to shipment
- Designed to work with standard building hardware, factory installed if desired
- Ease of operation conforms to ADA
- Available in single-leaf, double-leaf and bi-fold designs
- Wood veneer finish available

**All door and frame components are tested as a complete assembly prior to shipment.**



8' x 8' STC 52 Double-Leaf Door  
Hampton, GA



16' x 20' STC 52 Double-Leaf Door with 6' x 12' roof hatch.  
Columbia, SC







8' x 10' STC 50  
Double Leaf Doors  
Bloomington, IL



Gen-Set Enclosure  
8' x 10' STC 50 Doors



4' x 7' Communicating Doors



10' x 10' Double Leaf Door  
Wausau, WI



Oversize Doors  
Anniston, GA

## Acoustic Performance Data

	1/3 Octave Band Center Frequency, Hz						
	125	250	500	1k	2k	4k	STC
Sound Transmission Loss Data, dB							
QS-45 - 2½" Thick - 11.2 PSF	29	33	41	48	48	50	45
QS-46 - 2½" Thick - 8.6 PSF	36	41	45	51	50	52	46
QS-50 - 2½" Thick - 10.1 PSF	37	42	50	49	51	55	50
QS-51 - 2½" Thick - 10.1 PSF	40	44	48	52	52	55	51
QS-52 - 2½" Thick - 10.5 PSF	40	44	50	53	54	56	52
QS-54 - 3½" Thick - 18.3 PSF	37	47	52	54	55	60	54
QS-56 - 3½" Thick - 20.9 PSF	38	46	55	55	60	63	56

All tests performed by an independent NVLAP accredited acoustical testing facility. The test method conforms with ASTM Designations E90-09 and E413-87

## Acoustic Performance Data

	1/3 Octave Band Center Frequency, Hz						
	125	250	500	1k	2k	4k	NIC
Sound Transmission Loss Data, dB							
QS-61-SAHP - 3½" Thick - 19.3 PSF	42	53	59	63	66	71	62
QS-64-SAHP - 5" Thick - 19.7 PSF	51	59	70	70	71	73	70

These are an NIC 62 and 70. Field testing results may vary due to Room Size, Configuration, and Room Acoustics.

## eNoise Control

129 Penn St

Westfield, IN 46074

Phone: 317.774.1900

email: [info@eNoiseControl.com](mailto:info@eNoiseControl.com)